

SeaRox SL 340



Marine Slab 80

Acoustic Insulation

Product description

SeaRox SL 340 is a semi-rigid slab of stone wool.
Excellent properties for easy handling and installation.

Application

SeaRox SL 340 is primarily used for sound insulation. Perfect in combination as comfort and high noise reduction.



Product Properties


	Performance		Norm
Thermal conductivity	T [°C]	10	EN 12667
	λ (W/mK)	0,034	
Nominal density	80 kg/m ³		EN 1602 / IMO
Compressive strength	-		EN 826
Fire classification	Non-combustible Low Flame-Spread Properties		Acc. IMO FTP code
Water absorption (short term)	<1 kg/m ²		EN 1609
Max. Application Temperature	Wool 250°C		-
Sound absorption directly mounted	$\alpha_w = 0,9$ Thickness: 50 mm	$\alpha_w = 0,95$ Thickness: 2x50 mm	ISO 354 (approximated) Evaluated after ISO 11 654
Facings	-		IMO A.653(16) (low flame - spread)

Dimensions

SeaRox SL 340

Thickness (mm): 50 Length (mm): 1000 Width (mm): 600

Local variations in standard dimensions might occur.



Rockwool Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.