

SeaRox SL 720



Marine Batts 32

Comfort Insulation

Product description

SeaRox SL 720 is a soft, lightweight slab made of stone wool. The product can be supplied with reinforced alu foil.

Application

SeaRox SL 720 is used for comfort insulation.



Product Properties


	Performance			Norm
	T [°C]	10	50	
Thermal conductivity	λ (W/mK)	0,036	0,045	EN 12667
Nominal density		32 kg/m ³		EN 1602 / IMO
Compressive strength		-		EN 826
Fire classification		Non-combustible Low Flame-Spread Properties		Acc. IMO FTP code
Water absorption (short term)		< 1 kg/m ²		EN 1609 AC
Max. Application Temperature		Wool 250°C Facing 80°C		-
Sound absorption directly mounted		$\alpha_w = 0,75$ Thickness: 50 mm		ISO 354 (approximated) Evaluated after ISO 11 654
Facings (on request)		Reinforced alu foil		IMO A.653(16) (low flame - spread)

Dimensions

SeaRox SL 720

Thickness (mm): 50, 100 Length (mm): 1000 Width (mm): 600

Local variations in standard dimensions might occur.



Rockwool Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.